

# VITREZINC 586

## TECHNICAL DATA SHEET

Zinc Rich Epoxy Primer



**A I Coatings VITREZINC 586** is a Two Pack Zinc Rich primer for use on blast cleaned steel to give excellent adhesion and a tough and abrasion resistant film. The rich zinc content in this coating will give good cathodic protection. V586 can be overcoated with a suitable intermediate and topcoat to achieve a very durable and protective coating system. The coating is Type 2 Organic, with Level 1 zinc content of >85% w/w in the dry film.

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                  |             |           |            |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|-------------|-----------|------------|
| <b>USES &amp; BENEFITS</b> | As a primer on blast cleaned steel for: • Structural and architectural steel • Power plants and oil refineries • Transport and rolling stock • Touch up primer for inorganic zinc coatings • Mines and Petro-chemical plant                                                                                                                                                                                                                              |                                                                  |             |           |            |
|                            | <p>Benefits</p> <div>1. Suitable for repair of welded joints on zinc coated surfaces where abrasive blasting is not practical.</div> <div>2. Fast recoat times</div> <div>3. Subsequent coatings can be a choice of epoxy, polyurethane, acrylic or vinyl depending on area of use. Complies with AS 3750-9 T</div> <div>4. Complies with AS 2312 system guides</div> <div>5. Australian owned and manufactured</div> <div>6. Convenient packaging</div> |                                                                  |             |           |            |
| <b>PHYSICAL PROPERTIES</b> | Vehicle Type                                                                                                                                                                                                                                                                                                                                                                                                                                             | Two component epoxy                                              |             |           |            |
|                            | Hardener                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Polyamide                                                        |             |           |            |
|                            | Mixing Ratio                                                                                                                                                                                                                                                                                                                                                                                                                                             | 3 : 1 (Part A : Part B) by Volume                                |             |           |            |
|                            | Pot Life                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 8 Hrs @23°C (Do not use beyond pot life)                         |             |           |            |
|                            | Finish                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Flat                                                             |             |           |            |
|                            | Theoretical Coverage                                                                                                                                                                                                                                                                                                                                                                                                                                     | 13.2 – 7.0 m <sup>2</sup> / Litre @ 40 – 75µm DFT (75-142µm WFT) |             |           |            |
|                            | Volume Solids                                                                                                                                                                                                                                                                                                                                                                                                                                            | 53 ± 2 %                                                         |             |           |            |
|                            | Recommended DFT                                                                                                                                                                                                                                                                                                                                                                                                                                          | 50µm – 125 DFT                                                   |             |           |            |
|                            | Usual No. of Coats                                                                                                                                                                                                                                                                                                                                                                                                                                       | 1 to 2                                                           |             |           |            |
|                            | Colour                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Grey                                                             |             |           |            |
|                            | Pigmentation                                                                                                                                                                                                                                                                                                                                                                                                                                             | Metallic Zinc                                                    |             |           |            |
|                            | Product Weight                                                                                                                                                                                                                                                                                                                                                                                                                                           | 2.5 – 2.8 Kg/Litre (after mixing)                                |             |           |            |
| <b>ENGINEERING DATA</b>    | Abrasion Resistance                                                                                                                                                                                                                                                                                                                                                                                                                                      | Good                                                             |             |           |            |
|                            | Flexibility                                                                                                                                                                                                                                                                                                                                                                                                                                              | Good                                                             |             |           |            |
|                            | Solvent Resistance                                                                                                                                                                                                                                                                                                                                                                                                                                       | Very Good                                                        |             |           |            |
|                            | Water Resistance                                                                                                                                                                                                                                                                                                                                                                                                                                         | Excellent                                                        |             |           |            |
|                            | Durability                                                                                                                                                                                                                                                                                                                                                                                                                                               | Excellent                                                        |             |           |            |
| <b>CURING DATA</b>         | Substrate Temp.(°C)                                                                                                                                                                                                                                                                                                                                                                                                                                      | Surface Dry                                                      | Through Dry | Full Cure | Recoat Min |
|                            | 10°C                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 30 Min                                                           | 2.5 Hrs     | 7 Days    | 3 Hrs      |
|                            | 23°C                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 15 Min                                                           | 1.5 Hrs     | 5 Days    | 2 Hrs      |
|                            | 40°C                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 6 Min                                                            | 50 Min      | 3 Days    | 1.5 Hrs    |

# VITREZINC 586

## TECHNICAL DATA SHEET

Zinc Rich Epoxy Primer



|                     |                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| APPLICATION DATA    | General                                                                                                                                                                                                                                                | The temperature of the substrate should be min.3° C above the dew point of the air, and min 5°C as the curing process will be considerably retarded at lower temperatures. It is recommended to measure temperature and humidity in the vicinity of the substrate.                                                                                                                                 |
|                     | Mixing                                                                                                                                                                                                                                                 | Mix Part A and Part B in a ratio of 3:1 by volume and stir thoroughly                                                                                                                                                                                                                                                                                                                              |
|                     | Application                                                                                                                                                                                                                                            | Airless spray, Brush may be used for touching up. Pressure at Nozzle – 15 Mpa min(150 kp/cm²,2100 psi) Nozzle tip 0.38 – 0.53 mm (0.015 – 0.021")                                                                                                                                                                                                                                                  |
|                     | Cleaning                                                                                                                                                                                                                                               | V122 Epoxy Thinners.                                                                                                                                                                                                                                                                                                                                                                               |
|                     | Thinning                                                                                                                                                                                                                                               | V122 Epoxy Thinners (Thinning not normally required).                                                                                                                                                                                                                                                                                                                                              |
| SURFACE PREPARATION | Steel                                                                                                                                                                                                                                                  | Degrease the surface according to SSPC SP1 solvent cleaning. Round off rough welds and sharp edges and remove weld spatter and flux. Abrasive blast clean in accordance with AS 1627.9 to class 2½ minimum. Blast to achieve a 25–50-micron anchor profile. If profile is greater, additional film thickness is required for equivalent protection. Remove abrasive residue and dust from surface. |
| WORK STOPPAGES      | General                                                                                                                                                                                                                                                | Do not allow material to remain in hoses, gun or spray equipment. Thoroughly flush all equipment with A & I Coatings recommended cleaner. Once units of paint have been mixed they should not be resealed and it is advised that after prolonged stoppages work recommences with freshly mixed units.                                                                                              |
|                     | Clean Up                                                                                                                                                                                                                                               | Clean all equipment after use with A & I Coatings recommended cleaner. It is good work practice to periodically flush out spray equipment during the course of the working day. Frequency of cleaning will depend upon amount sprayed, temperature and elapsed time, (including delays).                                                                                                           |
| PACKING & STORAGE   | Packing                                                                                                                                                                                                                                                | Available in 8 L kits. For availability of other sizes, contact A & I Coatings.                                                                                                                                                                                                                                                                                                                    |
|                     | Storage                                                                                                                                                                                                                                                | 12 months if stored in sealed containers away from heat and moisture. Subject to re-inspection thereafter.                                                                                                                                                                                                                                                                                         |
| HEALTH & SAFETY     | All applicable statutory regulations must be observed in the application of this product. Users must first read the Safety Data Sheet for Vitrezinc 586. Users should familiarize themselves with all the safety aspects of the product prior to usage |                                                                                                                                                                                                                                                                                                                                                                                                    |

All surplus materials and empty containers should be disposed of in accordance with appropriate regional regulations/legislation. Note: The figures quoted for pot life and drying/curing times are not definitive. They are dependent on onsite conditions, such as volume of material mixed, ambient and substrate temperatures, weather and ventilation. DISCLAIMER Since the use and application of this product is beyond our control, we cannot be held responsible for product field performance. The information presented above is the result of our considerable experience with this product but is not to be construed as a performance warranty. For additional information, phone our Customer Service Centre.



PO Box 820 Moss Vale, NSW 2577

7 Lackey Road Moss Vale NSW 2577

Australia 1800 819 585

International +61 2 4869 1441

Fax +61 2 4868 3031

Email [helpdesk@aicoatings.com](mailto:helpdesk@aicoatings.com)

[www.aicoatings.com.au](http://www.aicoatings.com.au)